

MD5060e

5 kV INSULATION TESTER



- ✓ MICROPROCESSOR-CONTROLLED
- ✓ INSULATION TEST UP TO 5 TΩ
- ✓ AUTO-RANGE
- ✓ GUARD TERMINAL
- ✓ DIGITAL & BARGRAPH READING
- ✓ AUTOMATED TESTS:
 - ABSORPTION INDEX
 - POLARIZATION INDEXES
- ✓ PROGRAMMABLE TIMER
- ✓ PROGRAMMABLE PASS-FAIL
- ✓ REAL TIME CLOCK
- ✓ 4000 READINGS MEMORY
- ✓ USB INTERFACE
- ✓ RECHARGEABLE BATTERY

The MEGABRAS MD-5060e is a smart, microprocessor-controlled, 5kV insulation tester. Besides the conventional measurement of insulation resistances up to 5TΩ, its advanced features allow to automatically measure both the Polarization Index and Dielectric Absorption Index, thus significantly simplifying testing of transformers.

This insulation tester is a portable, battery-powered equipment. Test voltage may be chosen from 500V to 5kV in 500V increments. Due to its measurement principle (actual voltage and current readings) the accuracy of resistance measurement is not affected by any test voltage error.

The built-in chronometer automatically counts the elapsed time since the start of measurement. Measured values are transmitted through the USB interface. Furthermore, the measured values are stored in a non-volatile internal memory. Up to 4000 measurements may be stored, to be transferred afterward to a computer running the MegaLogg2 program. This software allows a further analysis of the test results, including a graphical representation and automatic report generation. The real time clock and calendar, and the sequential test number, facilitates the identification of each test, and the organization of a predictive maintenance system by trend analysis.

Some other advanced features are useful to run the most sophisticated insulation analysis. Configurable Pass-Fail and timed measurements are automatically performed, with a very simple and user-friendly setup. The measurement parameters are stored in the non-volatile memory for an easy configuration.

In order to guarantee the operator safety, the cabinet is made of a high breakdown strength plastic. High security output terminals are placed in the furthest and most protected area of the equipment. A light indicator shows high-voltage presence and is switched-off when the capacities (both internal and external) are discharged up to reaching a safe value.

MD-5060e is powered using a rechargeable battery and has an automatic charger that may be connected to 100 - 240V mains supply. The cabinet is strong and lightweight, easy to carry, impact-resistant and suitable to be used under severe weather conditions. Thus the equipment supplies very reliable and accurate measurements both in laboratory and out in the field.

MD5060e - TECHNICAL SPECIFICATIONS

TEST VOLTAGES

500 V, 1000 V, 2500 V, 5000 V directly, one button selectable.
500 V to 5 kV in 500 V increments.
DC, negative.

MAXIMUM RESISTANCE READING

5 TΩ @ 5 kV.

SHORT CIRCUIT CURRENT

1.5 ± 0.5 mA.

TEST VOLTAGES ACCURACY

± 3% of nominal test voltages on R ≥ 10 GΩ.

EQUIPMENT BASIC ACCURACY

± 5% of reading ± 3 digits.
(1 MΩ to 500 GΩ at any test voltage).

ADVANCED FEATURES

- Automated Polarization Index calculation.
- Automated Dielectric Absorption Ratio calculation.
- Programmable Pass-Fail test.
- Programmable Timer.

BUILT-IN PRINTER (OPTIONAL)

Prints elapsed time, actual voltage and resistance measured each 15 seconds.

BUILT-IN MEMORY

Stores up to 4000 insulation measurements.

INTERFACE

USB.

BUILT-IN CHRONOMETER

Shows elapsed time in mm:ss format. Count starts automatically for each measurement.

REAL TIME CLOCK AND CALENDAR

Allows a reliable identification for each test.

MEGALOGG2 SOFTWARE

Friendly, easy to use, software. Tests are represented in graphic and tabular views. With automatic report generator, including the operator's commentaries.

ENVIRONMENTAL PROTECTION

IP54 with closed lid.

SAFETY CLASS

In accordance with IEC 61010-1.

E.M.C.

In accordance with IEC 61326-1.

ELECTROSTATIC IMMUNITY

In accordance with IEC 61000-4-2.

ELECTROMAGNETIC IRRADIATION IMMUNITY

In accordance with IEC 61000-4-3.

POWER SUPPLY

Internal rechargeable 12 V - 2.3 Ah battery.

BATTERY CHARGER

For 100 - 240 V~ mains supply.

OPERATING TEMPERATURE RANGE

-5°C to 50°C.

STORAGE TEMPERATURE RANGE

-25°C to 65°C.

HUMIDITY RANGE

95% RH (non condensing).

EQUIPMENT WEIGHT

Approx. 3.6 kg.

DIMENSIONS

274 x 250 x 124 mm.

INCLUDED ACCESSORIES

- Set of 3 test leads (1.8 m)
- USB cable
- MegaLogg2 software
- Carrying bag
- Charger power cord.
- User guide.



MARK

Subject to technical change without notice. This catalogue is not a contractual document.



MEGABRAS INDÚSTRIA ELETRÔNICA LTDA.

Rua Gibraltar, 172 - Santo Amaro - CEP 04755-070

São Paulo - SP - Brazil

Phone +55 11 5641-8111

megabras@megabras.com - www.megabras.com



I10122802